

ALTERNATING CURRENT (AC)



AVAILABLE 7 kW

4,3 inches color touch screen
Wall and floor mounting,
Output connector :

AVAILABLE 22 kW

4,3 inches color touch screen
Floor mounting,
Output connector :



Type 1

or



Type 2

ALL IN ONE DIRECT CURRENT (DC) AND ALTERNATING CURRENT (AC)



AVAILABLE UP TO 50 kW

Fast charging
7 inches color touch screen
Floor mounting
Upto 42 inches front LCD for
advertising media (Optional)
Output connector :

AVAILABLE UP TO 30 kW

Fast charging
7 inches color touch screen
Floor mounting
Upto 42 inches front LCD for
advertising media (Optional)



AVAILABLE UP TO 60 kW

Fast charging
7 inches color touch screen
Floor mounting
Upto 42 inches front LCD for
advertising media (Optional)
Output connector :

AVAILABLE UP TO 150 kW

Fast charging
7 inches color touch screen
Floor mounting
Upto 42 inches front LCD for
advertising media (Optional)



CCS2



Type 2



CHAdeMO

FUNCTION

- > EASY TO INSTALL AND OPERATE
 - > HIGH EFFICIENCY, RELIABLE AND STABLE PERFORMANCE
 - > SUPPORT MULTIPLE CHARGING
 - > CUSTOMABLE PAYMENT METHODS
 - > ETHERNET OR WIRELESS (3G/4G, GPRS & WIFI (OPTIONAL))
 - > RFID CARD / OCPP (OPTIONAL)
 - > ONLINE DATA UPDATE
 - > IP 54 (Other IP class available upon request)
- > EQUIPPED WITH SAFETY FEATURES
 - OVERCURRENT
 - VOLTAGE DROP
 - RESIDUAL FLOW
 - PULSE VOLTAGE
 - LEAKAGE CURRENT
 - SHORTCIRCUIT CURRENT
 - OVER TEMPERATURE

USAGE CLASSIFICATIONS

Charging Classification	Charging Capacity	Charging Location
Charging Points	AC 7kW, 22kW	Commercial Buildings Residential
Charging Hubs	AC 7kW, 22kW	Estates Public Accesses
Charging Stations	DC 22kW, 50kW, 150kW, 180kW > 350kW	Public Accesses Toll Roads Circuit



Disclaimer: All specs and design subject to change depending on requirements and the needs without notice.